



## ***300Mbps Wireless N PCI Adapter***

**PCI  
32bit**

**300  
Mbps**

**2x2dBi  
Detachable  
Antenna**

**802.11  
compatible** **b g n**



- **High Speed up to 300Mbps**
- **PCI 32bit Plug and Play**
- **Supports Windows XP/Vista/7/Linux/MAC**
- **Supports WEP 64/128, WPA/WPA2**

**K-3000PCI**

## 150Mbps WIRELESS N PCI ADAPTER

<b>Model No.</b>	<b>K-3000PCI</b>
<b>Chipset</b>	<b>Ralink RT3062F</b>
<b>Standards</b>	<b>IEEE 802.11b, IEEE 802.11g, IEEE 802.11n</b>
<b>Interface</b>	<b>PCI 32bit ver. 2.2 interface</b>
<b>Antenna Type</b>	<b>2x2dBi SMA Type Omni detachable antenna</b>
<b>Wireless Frequency</b>	<b>2.412GHz-2.4835GHz</b>
<b>Output Power</b>	<b>11n:14±1dbm; 11g:15±1dbm; 11b:18±1dbm</b>
<b>Modulation</b>	<b>DBPSK, DQPSK, CCK and OFDM (BPSK,QPSK,16-QAM/ 64-QAM)</b>
<b>Numbers of selectable channels</b>	<b>USA,Canada(FCC): 11 channels (2.412GHz-2.462GHz) Europe(CE): 13 channels (2.412GHz-2.472GHz) Japan: 14 channels (2.412GHz-2.4835GHz)</b>
<b>Security</b>	<b>64/128-bit WEP; WPA-PSK/WPA2-PSK(TKIP/AES)</b>
<b>Power</b>	<b>DC 3.3V, powered by BUS</b>
<b>Dimension</b>	<b>120mm(L) x 40mm(W)</b>
<b>Weight</b>	<b>50g</b>
<b>Temperature</b>	<b>0° to 50° C (operating), -20° to 70° C (storage)</b>
<b>Humidity</b>	<b>5% to 90 % (operating), 5% to 90% (storage)</b>
<b>Certification</b>	<b>FCC Part 15 Class B, CE Mark</b>



For more information, please visit:  
[www.kozumi-usa.com](http://www.kozumi-usa.com)